

# KIMBER

## WOOD SHIVERS

Distributed By:

**Crown Machinery, LLC**

Office: 256.218.3045 ~ Fax: 256.218.3062

[www.crownmachinery.us](http://www.crownmachinery.us)

### Technical Details

Log Box (standard)	100" Long x 30" Wide x 48" Deep (85 cu/ft)
Log Box Power	Two 124" Hydraulic Cylinders
Hydraulic Pump	50 hp with Cooling Loop
Cutter Head	10" diameter x 30" long (Two per machine)
Cutting Tools	10 Knives per Cutter Head
Head Speed	2400 RPM
Shaving Size	Three points to adjust shavings integrity
Head Motors	50 hp w/optional 75 hp
Head Maintenance	WHead completely slide out to the side for safe maintenance
Capacity (estimated)	2.75-3.5 tons of green shavings per hour
Shavings Outlet	Gravity Discharge from cutter heads to belt conveyor
MCC (optional)	460/480V AC 300amp Motor Control Center
Control Power	120V
Control Panel	Floor standing panel
Weight (Approx)	14,000 lbs.
Overall Dimensions	23' Long x 4' Wide (excluding slide) x 10' High
Noise Levels	In excess of 95 DBA; hearing protection will be required
Warranty	One Year Limited
Delivery	12-14 working weeks
Freight	FOB Scottsboro, AL USA

### KIMBER 2308 Log Shaver Two 30" Head Machine

### KIMBER 4488 Log Shaver Four 48" Head Machine

100" Long x 48" Wide x 48" Deep (136 cu/ft)
Two 124" Hydraulic Cylinders
50 hp with Cooling Loop
10" diameter x 48" long (Four per machine)
20 Knives per Cutter Head
2400 RPM
Three points to adjust shavings integrity
75 hp each head
Head completely slide out to the side for safe maintenance
8.5-10 tons of green shavings per hour
Gravity Discharge from cutter heads to belt conveyor
460/480V AC 600amp Motor Control Center
120V
Floor standing panel
23,000 lbs.
22'4" Long x 5'6" Wide (excluding slide) x 10' High
In excess of 95 DBA; hearing protection will be required
One Year Limited
12-14 working weeks
FOB Scottsboro, AL USA

### KIMBR 2488 Log Shaver Two 48" Head Machine

100" Long x 48" Wide x 48" Deep (136 cu/ft)
Two 124" Hydraulic Cylinders
50 hp with Cooling Loop
10" diameter x 48" long (Two per machine)
20 Knives per Cutter Head
2400 RPM
Three points to adjust shavings integrity
75 hp each head
Head completely slide out to the side for safe maintenance
4.2-5.8 tons of green shavings per hour
Gravity Discharge from cutter heads to belt conveyor
460/480V AC 300amp Motor Control Center
120V
Floor standing panel
17,000 lbs.
23' Long x 5'6" Wide (excluding slide) x 10' High
In excess of 95 DBA; hearing protection will be required
One Year Limited
12-14 working weeks
FOB Scottsboro, AL USA



# KIMBER

## WOOD SHIVERS



[www.crownmachinery.us](http://www.crownmachinery.us)

[www.crownmachinery.us](http://www.crownmachinery.us)